



Showtec NET-2/5 Pocket 2-Channel Art-Net node - 5-pin XLR

Compact and Reliable

The NET-2/5 Pocket is small enough for tight spaces but solid enough for demanding installs.

POE-Powered for Simple Cabling

Runs via Power over Ethernet, eliminating the need for a separate 12V power supply. Useful when mains access is limited or tidy cable runs are a priority.

Art-Net & sACN to DMX Conversion

Supports two DMX universes (1024 channels) over a single CAT5. Converts Art-Net or sACN to DMX512, and back, making it ideal for pixel-mapped rigs or distributed control networks.

Local and Remote Configuration

Adjust settings using the onboard display and buttons or connect via browser for remote setup and tweaks. Default login: Admin / Admin.

Technical Specifications

Power Supply	100-240 V AC 50/60 Hz (Power adapter)
Power over Ethernet (PoE)	Yes
Power Consumption	8 W
Power Connector In	Low Voltage DC Plug
DMX Connector	XLR 5P In/Out
DMX Connector In	XLR 5P
DMX Connector Out	XLR 5P
Data Connector In	etherCON
Adapter type	AC-DC adapter
Input voltage	100-240 V AC, 50/60 Hz
Output voltage	12 V DC
Length (mm)	115 mm (4.528")
Width (mm)	67 mm (2.638")
Height (mm)	44 mm (1.732")
Weight	0.3 kg (0.661 lb)
IP Rating	IP20 (indoor use only)
Housing	Metal, Plastic
LED Indicators	Operation mode, Power, Signal
Maximum Ambient Temperature	40 °C (104 °F)
Minimum Ambient Temperature	-5 °C (23 °F)
Warranty	1 Year

Package Contents

- Showtec Net-2/5 Pocket
- AC power adapter
- User Manual