



Showtec NET-8/5

8-Channel Art-Net/Kling-Net node - 5-pin XLR

Supports Up to 4096 DMX Channels

Handles 8 isolated DMX512 universes, transporting up to 4096 channels over a single CAT5 cable. Perfect for small to large-scale events or complex installations.

Bi-Directional Art-Net to DMX Conversion

Converts Art-Net to DMX512 and back, allowing flexible routing of data inputs and outputs for diverse lighting setups.

Built-In Network Switch

Includes an integrated Ethernet repeater switch, simplifying network setup and reducing the need for extra hardware on site.

User-Friendly Configuration

Features an onboard display and buttons for direct setup, plus remote access through a web browser with a simple interface (default login: Admin / Admin).

Technical Specifications

Power Supply	100-240 V AC 50/60 Hz
Power Consumption	20 W
Power Connector In	Power Pro Blue
DMX Connector	XLR 5P Out
DMX Connector In	XLR 5P
DMX Connector Out	XLR 5P
Data Connector In	etherCON
Data Connector Out	etherCON
Input voltage	100-240 V AC, 50/60 Hz
Length (mm)	483 mm (19.016")
Width (mm)	143 mm (5.63")
Height (mm)	46 mm (1.811")
Weight)	2.2 kg (4.85 lb)
Installation Depth (Excl. Connector)	143 mm (5.63")
Rack Units	1 U
IP Rating	IP20 (indoor use only)
Housing	Metal, Plastic
LED Indicators	Operation mode, Power, Signal
Maximum Ambient Temperature	40 °C (104 °F)
Minimum Ambient Temperature	-5 °C (23 °F)
Warranty	1 Year

Package Contents

- Showtec Net-8/5
- Schuko to Pro power connector power cabls (1.3m)
- User Manual